



# RC filter




**Fig. 2.1** RC filter.

# Differential equation




# Differential equation



Voltage balance?


# Differential equation



Voltage balance?

$$RI(t) + y(t) = x(t)$$

# Differential equation




Voltage balance?

$$RI(t) + y(t) = x(t)$$

Current through resistor  $R$  and capacitance  $C$ :

$$I(t) = C\dot{y}(t)$$

# Differential equation




Voltage balance?

$$RI(t) + y(t) = x(t)$$

Current through resistor  $R$  and capacitance  $C$ :

$$I(t) = C\dot{y}(t)$$

# Differential equation



Voltage balance?

$$RI(t) + y(t) = x(t)$$


Current through resistor  $R$  and capacitance  $C$ :

$$I(t) = C\dot{y}(t)$$



$$RC\dot{y}(t) + y(t) - x(t) = 0$$

# Differential equation



Voltage balance?

$$RI(t) + y(t) = x(t)$$

Current through resistor  $R$  and capacitance  $C$ :

$$I(t) = C\dot{y}(t)$$



$$RC\dot{y}(t) + y(t) - x(t) = 0$$

**First order linear differential equation**

# Linearity

**Input**

**Output**

# Linearity

**Input**

$x_1(t)$



**Output**

$y_1(t)$

# Linearity

**Input**

**Output**

$x_1(t)$



$y_1(t)$

$x_2(t)$



$y_2(t)$

# Linearity

**Input**

**Output**

$$x_1(t)$$



$$y_1(t)$$

$$x_2(t)$$



$$y_2(t)$$

$$x_3(t) = a x_1(t) + b x_2(t)$$



$$y_3(t) = ?$$

# Linearity

**Input**

**Output**

$$x_1(t)$$



$$y_1(t)$$

$$x_2(t)$$




$$y_2(t)$$

$$x_3(t) = a x_1(t) + b x_2(t)$$



$$y_3(t) = ?$$

Property of  
linear system: 

# Linearity

**Input**

**Output**

$$x_1(t)$$



$$y_1(t)$$

$$x_2(t)$$




$$y_2(t)$$

$$x_3(t) = a x_1(t) + b x_2(t)$$



$$y_3(t) = ?$$

Property of  
linear system:



$$y_3(t) = a y_1(t) + b y_2(t)$$

# Linearity

**Input**

**Output**

$$x_1(t)$$



$$y_1(t)$$

$$x_2(t)$$




$$y_2(t)$$

$$x_3(t) = a x_1(t) + b x_2(t)$$



$$y_3(t) = ?$$

Property of  
linear system:



$$y_3(t) = a y_1(t) + b y_2(t)$$

RC filter = linear (time invariant) system = LTI system

# Frequency response function and Fourier transform

# Frequency response function and Fourier transform

$$RC\dot{y}(t) + y(t) - x(t) = 0 \quad \text{for zero input signal } x(t)$$

# Frequency response function and Fourier transform

$$RC\dot{y}(t) + y(t) - x(t) = 0 \quad \text{for zero input signal } x(t)$$

$$x(t) = 0: \implies RC\dot{y}(t) + y(t) = 0$$

# Frequency response function and Fourier transform

$$RC\dot{y}(t) + y(t) - x(t) = 0 \quad \text{for zero input signal } x(t)$$

$$x(t) = 0: \implies RC\dot{y}(t) + y(t) = 0$$

$$\text{Solution: } y(t) = -\frac{1}{RC} \cdot e^{-\frac{t}{RC}}$$

# Frequency response function and Fourier transform

$$RC\dot{y}(t) + y(t) - x(t) = 0 \quad \text{for zero input signal } x(t)$$

$$x(t) = 0: \implies RC\dot{y}(t) + y(t) = 0$$

$$\text{Solution: } y(t) = -\frac{1}{RC} \cdot e^{-\frac{t}{RC}}$$

What is the solution to **arbitrary** input signals ?

# Frequency response function and Fourier transform

$$RC\dot{y}(t) + y(t) - x(t) = 0 \quad \text{for zero input signal } x(t)$$

$$x(t) = 0: \implies RC\dot{y}(t) + y(t) = 0$$

$$\text{Solution: } y(t) = -\frac{1}{RC} \cdot e^{-\frac{t}{RC}}$$

What is the solution to **arbitrary** input signals ?

**Approach:** Solve for harmonic signals,  
then construct arbitrary signals from harmonic signals.

# Frequency response function and Fourier transform

$$RC\dot{y}(t) + y(t) - x(t) = 0 \quad \text{for zero input signal } x(t)$$

$$x(t) = 0: \implies RC\dot{y}(t) + y(t) = 0$$

$$\text{Solution: } y(t) = -\frac{1}{RC} \cdot e^{-\frac{t}{RC}}$$

What is the solution to **arbitrary** input signals ?

**Approach:** Solve for harmonic signals,  
then construct arbitrary signals from harmonic signals.

 „Fourier transform“

# Fourier transform

# Fourier transform

Definition:

$$\mathbf{F} \{x(t)\} = X(f) = \int_{-\infty}^{\infty} x(t) e^{-j2\pi ft} dt$$

# Fourier transform

Definition:  $\mathbf{F} \{x(t)\} = X(f) = \int_{-\infty}^{\infty} x(t) e^{-j2\pi ft} dt$

Common practice to write (with  $\omega = 2\pi f$ ):  $X(j\omega) = \int_{-\infty}^{\infty} x(t) e^{-j\omega t} dt$

# Fourier transform

Definition:  $\mathbf{F} \{x(t)\} = X(f) = \int_{-\infty}^{\infty} x(t) e^{-j2\pi ft} dt$

Common practice to write (with  $\omega = 2\pi f$ ):  $X(j\omega) = \int_{-\infty}^{\infty} x(t) e^{-j\omega t} dt$

Back transformation:  $x(t) = \frac{1}{2\pi} \int_{-\infty}^{\infty} X(j\omega) e^{j\omega t} d\omega$

# Transform properties of the Fourier transform

( $\Leftrightarrow$  indicates a transform pair,  $x(t) \Leftrightarrow X(j\omega)$ ):

# Transform properties of the Fourier transform

( $\Leftrightarrow$  indicates a transform pair,  $x(t) \Leftrightarrow X(j\omega)$ ):

- *Time shifting* —  $x(t - a) \Leftrightarrow X(j\omega) \cdot e^{-j\omega a}$

# Transform properties of the Fourier transform

( $\Leftrightarrow$  indicates a transform pair,  $x(t) \Leftrightarrow X(j\omega)$ ):

• *Time shifting* —  $x(t - a) \Leftrightarrow X(j\omega) \cdot e^{-j\omega a}$

• *Derivative* —  $\frac{d}{dt}x(t) \Leftrightarrow j\omega \cdot X(j\omega)$

# Transform properties of the Fourier transform

( $\Leftrightarrow$  indicates a transform pair,  $x(t) \Leftrightarrow X(j\omega)$ ):

• *Time shifting* —  $x(t - a) \Leftrightarrow X(j\omega) \cdot e^{-j\omega a}$

• *Derivative* —  $\frac{d}{dt}x(t) \Leftrightarrow j\omega \cdot X(j\omega)$

• *Integration* —  $\int_{-\infty}^{\infty} x(t)dt \Leftrightarrow \frac{1}{j\omega} \cdot X(j\omega)$


# Convolution

# Convolution

$$g(t) = f(t) * h(t) = \int_{-\infty}^{\infty} f(\tau) \cdot h(t - \tau) d\tau$$

# Convolution

$$g(t) = f(t) * h(t) = \int_{-\infty}^{\infty} f(\tau) \cdot h(t - \tau) d\tau$$




**Fig. 2.5** Graphical interpretation of the convolution operation.

# Convolution

$$g(t) = f(t) * h(t) = \int_{-\infty}^{\infty} f(\tau) \cdot h(t - \tau) d\tau$$

• *Convolution Theorem* —

$$f(t) * h(t) \Leftrightarrow F(j\omega) \cdot H(j\omega)$$



**Fig. 2.5** Graphical interpretation of the convolution operation.

# Harmonic input signals

# Harmonic input signals

$$RC\dot{y}(t) + y(t) - x(t) = 0 \quad \text{for harmonic input signal } x(t)$$

# Harmonic input signals

$$RC\dot{y}(t) + y(t) - x(t) = 0 \quad \text{for harmonic input signal } x(t)$$

Harmonic input signal:

# Harmonic input signals

$$RC\dot{y}(t) + y(t) - x(t) = 0 \quad \text{for harmonic input signal } x(t)$$

Harmonic input signal:  $x(t) = A_i e^{j\omega t}$

# Harmonic input signals

$$RC\dot{y}(t) + y(t) - x(t) = 0 \quad \text{for harmonic input signal } x(t)$$

Harmonic input signal:  $x(t) = A_i e^{j\omega t}$

Ansatz for the output signal:

# Harmonic input signals

$$RC\dot{y}(t) + y(t) - x(t) = 0 \quad \text{for harmonic input signal } x(t)$$

Harmonic input signal:  $x(t) = A_i e^{j\omega t}$

Ansatz for the output signal:  $y(t) = A_o e^{j\omega t}$   
 $\dot{y}(t) = j\omega A_o e^{j\omega t}$

# Harmonic input signals

$$RC\dot{y}(t) + y(t) - x(t) = 0 \quad \text{for harmonic input signal } x(t)$$


Harmonic input signal:

$$x(t) = A_i e^{j\omega t}$$

Ansatz for the output signal:

$$y(t) = A_o e^{j\omega t}$$

$$\dot{y}(t) = j\omega A_o e^{j\omega t}$$



$$A_o e^{j\omega t} (RCj\omega + 1) = A_i e^{j\omega t}$$

# Harmonic input signals

$$RC\dot{y}(t) + y(t) - x(t) = 0 \quad \text{for harmonic input signal } x(t)$$


Harmonic input signal:

$$x(t) = A_i e^{j\omega t}$$


Ansatz for the output signal:

$$y(t) = A_o e^{j\omega t}$$

$$\dot{y}(t) = j\omega A_o e^{j\omega t}$$



$$A_o e^{j\omega t} (RCj\omega + 1) = A_i e^{j\omega t}$$




$$\frac{A_o}{A_i} = \frac{1}{RCj\omega + 1} = T(j\omega)$$

# Harmonic input signals


$$RC\dot{y}(t) + y(t) - x(t) = 0 \quad \text{for harmonic input signal } x(t)$$

Harmonic input signal:  $x(t) = A_i e^{j\omega t}$

Ansatz for the output signal:  $y(t) = A_o e^{j\omega t}$   
 $\dot{y}(t) = j\omega A_o e^{j\omega t}$



$$A_o e^{j\omega t} (RCj\omega + 1) = A_i e^{j\omega t}$$



$$\frac{A_o}{A_i} = \frac{1}{RCj\omega + 1} = T(j\omega)$$

**Frequency response function**

# Input/output relation

$$A_o = T(j\omega) \cdot A_i$$

# Polar form

# Polar form

$$T(j\omega) = \frac{1}{RCj\omega + 1} \longrightarrow \text{polar form}$$

# Polar form

$$T(j\omega) = \frac{1}{RCj\omega + 1} \longrightarrow \text{polar form}$$

**Identities:**  $\frac{1}{\alpha + j\beta} = \frac{\alpha}{\alpha^2 + \beta^2} - j\frac{\beta}{\alpha^2 + \beta^2}$  and  $\Phi = \arctan\left(\frac{\text{Im}}{\text{Re}}\right)$

# Polar form

$$T(j\omega) = \frac{1}{RCj\omega + 1} \longrightarrow \text{polar form}$$

**Identities:**  $\frac{1}{\alpha + j\beta} = \frac{\alpha}{\alpha^2 + \beta^2} - j\frac{\beta}{\alpha^2 + \beta^2}$  and  $\Phi = \arctan\left(\frac{\text{Im}}{\text{Re}}\right)$

For:  $\frac{1}{\alpha + j\beta} : \Phi = \arctan\left(\frac{-\beta}{\alpha}\right)$  and  $|\dots| = \frac{1}{\sqrt{1 + (RC\omega)^2}}$

# Polar form

$$T(j\omega) = \frac{1}{RCj\omega + 1} \longrightarrow \text{polar form}$$

**Identities:**  $\frac{1}{\alpha + j\beta} = \frac{\alpha}{\alpha^2 + \beta^2} - j\frac{\beta}{\alpha^2 + \beta^2}$  and  $\Phi = \arctan\left(\frac{\text{Im}}{\text{Re}}\right)$

For:  $\frac{1}{\alpha + j\beta} : \Phi = \arctan\left(\frac{-\beta}{\alpha}\right)$  and  $|\dots| = \frac{1}{\sqrt{1 + (RC\omega)^2}}$

and  $T(j\omega) = \frac{1}{\sqrt{1 + (RC\omega)^2}} \cdot e^{j\Phi(\omega)}$

$$\Phi(\omega) = \arctan(-RC\omega) = -\arctan(RC\omega)$$

# **The frequency response and arbitrary input signals**

# The frequency response and arbitrary input signals

$A_i(j\omega) \rightarrow$  harmonic component of the Fourier spectrum  $X(j\omega)$  (input)

$A_o(j\omega) \rightarrow$  harmonic component of the Fourier spectrum  $Y(j\omega)$  (output)

# The frequency response and arbitrary input signals

$A_i(j\omega) \rightarrow$  harmonic component of the Fourier spectrum  $X(j\omega)$  (input)

$A_o(j\omega) \rightarrow$  harmonic component of the Fourier spectrum  $Y(j\omega)$  (output)

The frequency response function relates the Fourier spectrum of the output signal  $Y(j\omega)$  to the Fourier spectrum of the input signal  $X(j\omega)$  :

# The frequency response and arbitrary input signals

$A_i(j\omega) \rightarrow$  harmonic component of the Fourier spectrum  $X(j\omega)$  (input)

$A_o(j\omega) \rightarrow$  harmonic component of the Fourier spectrum  $Y(j\omega)$  (output)

The frequency response function relates the Fourier spectrum of the output signal  $Y(j\omega)$  to the Fourier spectrum of the input signal  $X(j\omega)$  :

$$T(j\omega) = \frac{Y(j\omega)}{X(j\omega)}$$

# The frequency response and arbitrary input signals

$A_i(j\omega) \rightarrow$  harmonic component of the Fourier spectrum  $X(j\omega)$  (input)

$A_o(j\omega) \rightarrow$  harmonic component of the Fourier spectrum  $Y(j\omega)$  (output)

The frequency response function relates the Fourier spectrum of the output signal  $Y(j\omega)$  to the Fourier spectrum of the input signal  $X(j\omega)$  :

$$T(j\omega) = \frac{Y(j\omega)}{X(j\omega)}$$

• **Definition** — The frequency response function  $T(j\omega)$  is defined as the Fourier transform of the output signal divided by the Fourier transform of the input signal.

# Input/output relation

Fourier spectrum of the filter output:

$$Y(j\omega) = T(j\omega) \cdot X(j\omega)$$

The frequency response function can be measured by comparing output and input signals to the system **without further knowledge of the physics going on inside the filter!**

# Transfer function and Laplace transform

Bilateral Laplace transform of  $f(t)$ :  $\mathbf{L} [f(t)] = \int_{-\infty}^{\infty} f(t) e^{-st} dt$

with the complex variable  $s = \sigma + j\omega$

# Transfer function and Laplace transform

Bilateral Laplace transform of  $f(t)$ :  $\mathbf{L} [f(t)] = \int_{-\infty}^{\infty} f(t)e^{-st} dt$

with the complex variable  $s = \sigma + j\omega$

$\mathbf{L} [f(t)]$  will be written as  $F(s)$ .

# Transfer function and Laplace transform

Bilateral Laplace transform of  $f(t)$ :  $\mathbf{L} [f(t)] = \int_{-\infty}^{\infty} f(t)e^{-st} dt$

with the complex variable  $s = \sigma + j\omega$

$\mathbf{L} [f(t)]$  will be written as  $F(s)$ .

**Property:**  $\mathbf{L} [\dot{f}(t)] = s \cdot F(s)$

# Transfer function and Laplace transform

# Transfer function and Laplace transform

Transforming equation  $RC\dot{y}(t) + y(t) - x(t) = 0$

using  $\mathbf{L} [\dot{f}(t)] = s \cdot F(s)$  we obtain:

# Transfer function and Laplace transform

Transforming equation  $RC\dot{y}(t) + y(t) - x(t) = 0$

using  $\mathbf{L} [\dot{f}(t)] = s \cdot F(s)$  we obtain:

$$RCsY(s) + Y(s) - X(s) = 0$$

# Transfer function and Laplace transform

Transforming equation  $RC\dot{y}(t) + y(t) - x(t) = 0$

using  $\mathbf{L} [\dot{f}(t)] = s \cdot F(s)$  we obtain:

$$RCsY(s) + Y(s) - X(s) = 0$$

with  $Y(s)$  and  $X(s)$  being the Laplace transforms of  $y(t)$  and  $x(t)$ , respectively.

# Transfer function and Laplace transform

Transforming equation  $RC\dot{y}(t) + y(t) - x(t) = 0$

using  $\mathbf{L} [\dot{f}(t)] = s \cdot F(s)$  we obtain:

$$RCsY(s) + Y(s) - X(s) = 0$$

with  $Y(s)$  and  $X(s)$  being the Laplace transforms of  $y(t)$  and  $x(t)$ , respectively.

$$\Rightarrow T(s) = \frac{Y(s)}{X(s)} = \frac{1}{1 + sRC} = \frac{1}{1 + s\tau}$$

# Transfer function and Laplace transform

Transforming equation  $RC\dot{y}(t) + y(t) - x(t) = 0$

using  $\mathbf{L} [\dot{f}(t)] = s \cdot F(s)$  we obtain:

$$RCsY(s) + Y(s) - X(s) = 0$$

with  $Y(s)$  and  $X(s)$  being the Laplace transforms of  $y(t)$  and  $x(t)$ , respectively.

$$\Rightarrow T(s) = \frac{Y(s)}{X(s)} = \frac{1}{1 + sRC} = \frac{1}{1 + s\tau} \quad \text{transfer function}$$

# Transfer function

- *Definition* — The transfer function  $T(s)$  is defined as the Laplace transform of the output signal divided by the Laplace transform of the input signal.

# Transfer function

- *Definition* — The transfer function  $T(s)$  is defined as the Laplace transform of the output signal divided by the Laplace transform of the input signal.

Laplace transform of the output signal:

# Transfer function

• *Definition* — The transfer function  $T(s)$  is defined as the Laplace transform of the output signal divided by the Laplace transform of the input signal.

Laplace transform of the output signal:

$$Y(s) = T(s)X(s)$$

# Transfer function

• *Definition* — The transfer function  $T(s)$  is defined as the Laplace transform of the output signal divided by the Laplace transform of the input signal.

Laplace transform of the output signal:

$$Y(s) = T(s)X(s)$$

RC Filter:

$$T(s) = \frac{1}{1 + s\tau}$$

# Transfer function

• *Definition* — The transfer function  $T(s)$  is defined as the Laplace transform of the output signal divided by the Laplace transform of the input signal.

Laplace transform of the output signal:

$$Y(s) = T(s)X(s)$$

RC Filter:

$$T(s) = \frac{1}{1 + s\tau}$$

Special cases:

# Transfer function

• *Definition* — The transfer function  $T(s)$  is defined as the Laplace transform of the output signal divided by the Laplace transform of the input signal.

Laplace transform of the output signal:

$$Y(s) = T(s)X(s)$$

RC Filter:

$$T(s) = \frac{1}{1 + s\tau}$$

Special cases:

a)  $s \rightarrow j\omega \Rightarrow T(s) \rightarrow T(j\omega)$

# Transfer function

• *Definition* — The transfer function  $T(s)$  is defined as the Laplace transform of the output signal divided by the Laplace transform of the input signal.

Laplace transform of the output signal:

$$Y(s) = T(s)X(s)$$

RC Filter:

$$T(s) = \frac{1}{1 + s\tau}$$

Special cases:

**a)**  $s \rightarrow j\omega \Rightarrow T(s) \rightarrow T(j\omega)$

**b)**  $s \rightarrow -\frac{1}{\tau} \Rightarrow T(s) \rightarrow \infty$

# Transfer function

• *Definition* — The transfer function  $T(s)$  is defined as the Laplace transform of the output signal divided by the Laplace transform of the input signal.

Laplace transform of the output signal:

$$Y(s) = T(s)X(s)$$

RC Filter:

$$T(s) = \frac{1}{1 + s\tau}$$

Special cases:

a)  $s \rightarrow j\omega \Rightarrow T(s) \rightarrow T(j\omega)$

b)  $s \rightarrow -\frac{1}{\tau} \Rightarrow T(s) \rightarrow \infty$  “pole”


# The impulse response function

Dirac delta 'function'  $\delta(t)$

$$\int_{-\infty}^{\infty} f(t)\delta(t - \tau)dt = f(\tau)$$

# The impulse response function

Dirac delta 'function'  $\delta(t)$   $\int_{-\infty}^{\infty} f(t)\delta(t - \tau)dt = f(\tau)$



From the conditions of unit area and infinitesimal duration we obtain

$$\int_{-\infty}^{\infty} \delta(t) dt = 1$$

and  $\delta(t) = 0$  for  $t \neq 0$

From the conditions of unit area and infinitesimal duration we obtain

$$\int_{-\infty}^{\infty} \delta(t) dt = 1$$

and  $\delta(t) = 0$  for  $t \neq 0$

**Properties**      $\mathbf{F} \{ \delta(t) \} = \int_{-\infty}^{\infty} \delta(t) \cdot e^{-j2\pi ft} dt = 1$

$$\mathbf{L} \{ \delta(t) \} = \int_{-\infty}^{\infty} \delta(t) \cdot e^{-st} dt = 1$$

# The impulse response function

Response of a filter to an impulsive (delta function) input signal.

Properties:

- The frequency response function  $T(j\omega)$  is the Fourier transform of the impulse response function.

- The transfer function  $T(s)$  is the Laplace transform of the impulse response function.

**Fourier spectrum of a filter output signal:**

**Fourier spectrum of a filter output signal:**

$$Y(j\omega) = T(j\omega) \cdot X(j\omega)$$

**Fourier spectrum of a filter output signal:**

$$Y(j\omega) = T(j\omega) \cdot X(j\omega)$$

**Convolution theorem:**

**Fourier spectrum of a filter output signal:**

$$Y(j\omega) = T(j\omega) \cdot X(j\omega)$$

**Convolution theorem:**

$$T(j\omega) \cdot X(j\omega) = H(j\omega) \cdot X(j\omega) \quad \Leftrightarrow \quad h(t) * x(t)$$

**Fourier spectrum of a filter output signal:**

$$Y(j\omega) = T(j\omega) \cdot X(j\omega)$$

**Convolution theorem:**

$$T(j\omega) \cdot X(j\omega) = H(j\omega) \cdot X(j\omega) \quad \Leftrightarrow \quad h(t) * x(t)$$

**Consequences:**


**Fourier spectrum of a filter output signal:**

$$Y(j\omega) = T(j\omega) \cdot X(j\omega)$$


**Convolution theorem:**

$$T(j\omega) \cdot X(j\omega) = H(j\omega) \cdot X(j\omega) \Leftrightarrow h(t) * x(t)$$

**Consequences:**



# The frequency response function and the pole position



**Fig. 2.10** Representation of the RC filter in the  $s$  plane. The pole location at  $-1/\tau$  is marked by an X.

Transfer function RC filter:

$$T(s) = \frac{1}{1 + s\tau} = \frac{1}{\tau} \left[ \frac{1}{(1/\tau) + s} \right]$$

For  $s = j\omega$ ,  $\omega$  moves along the imaginary axis

$1/\tau + j\omega$  represents the vector  $\vec{\rho}(\omega)$

$$\Rightarrow T(j\omega) = \frac{1}{\tau} \left[ \frac{1}{(1/\tau) + j\omega} \right]$$

which is pointing from the pole position towards the actual frequency on the imaginary axis.

# in polar coordinates

$$T(j\omega) = \frac{1}{\tau} \left[ \frac{1}{|\vec{\rho}(\omega)| e^{j\Theta}} \right] = \frac{1}{\tau} \left[ \frac{1}{|\vec{\rho}(\omega)|} e^{-j\Theta(j\omega)} \right] = |T(j\omega)| e^{j\Phi(j\omega)}$$

For the given example, the amplitude value of the frequency response function for frequency  $\omega$  is proportional to the reciprocal of the length of the vector  $\vec{r}(\omega)$  from the pole location to the point  $j\omega$  on the imaginary axis. The phase angle equals the negative angle between  $\vec{r}(\omega)$  and the real axis.

## Problem 2.2

Determine graphically the amplitude characteristics of the frequency response for a RC filter with  $R = 4.0 \text{ Ohm}$  and  $C = (1.25/2\pi) F = 0.1989495 F$  ( $1\text{Ohm} = 1(V/A)$ ,  $1F = 1As/V$  ). Where is the pole position in the S plane? For the plot use frequencies between 0 and 5 Hz.


## Problem 2.3

Calculate the frequency response for the RC filter from Problem 2.2 using the Digital Seismology Tutor.

Start up: Digital Seismology Tutor

# Solution 2.2

*Solution 2.2* The pole position is at  $-1/\tau$ .  $\tau = R C = 4.0 \text{ Ohm } 0.1989495F$  which is  $4.0 \text{ V/A } 0.1989495Asec/V = 0.795798sec$ . Hence, the pole is at  $-1.2566 \text{ (rad/s)}$ . For each point on the imaginary axis (angular frequency axis), determine the reciprocal of the length of the vector from the pole to that point. You can do this either by using a ruler and graph paper or simply by exploiting analytical geometry. Plot this value as a function of angular frequency or frequency, respectively. Below, the procedure is demonstrated schematically for a frequency of 1Hz (Fig. A 2.1; note, that Fig. A 2.1 is not on 1:1 scale).



**Example: f=1 Hz**

$$\omega = 2\pi \cdot 1 = 6,2832$$

$$|\vec{\rho}(2\pi)| = 6,4076$$

$$|T(j2\pi)| = \frac{1}{\tau} \left[ \frac{1}{|\vec{\rho}(\omega)|} \right]$$


$$|T(j2\pi)| = \frac{1,2566}{6,4076} = 0,1961$$

**Fig. A 2.1** Graphical determination of the modulus of the frequency response function for the RC filter of Problem 2.2. The plot demonstrates the evaluation for a frequency of 1 Hz.

# Solution 2.3

*Solution 2.3* The Digital Seismology Tutor (DST) simulates the action of systems defined by their transfer function in the complex s-plane. As we will see later in more detail, a transfer function of a more general system can have more than one pole as well as a number of zeros (at which the transfer function becomes zero). The positions of poles and zeros define the transfer function completely. In order to do the filtering, DST needs to know the position(s) of the pole(s) and zero(s) (which will be introduced in later chapters) in the complex s-plane.

After starting up the DST, select the *Modify and Enter* option from the *Poles/Zeros* menu. In order to enter the pole position for the RC-filter at  $(-1.2566, 0)$ , enter the real part ( $-1.2566$ ) into the uppermost left box and the imaginary part ( $0.0$ ) into the uppermost right box as shown in Fig. A 2.2. Enter a  $1.0$  for the scale factor in the bottom box. Finally accept the input either by using the *OK* or the *Apply* button. The difference between these two is merely that the *OK* button closes the window after accepting the input while the *Apply* button leaves it open for further input.




	real part	imaginary part
POLES	-1.2566	0
ZEROS		
Scale Factor	1.0	

Ok Apply Reset Cancel

**Fig. A 2.2** How to enter the pole position for Problem 2.3 into the *Modify and Enter Poles/ Zero* panel of the DST.

# Solution 2.3, cont. 1


After you entered the pole into the DST, you can visualize its position within the complex s-plane by using the *Map* option from the *Poles/Zeros* menu (Fig. A 2.3).



**Fig. A 2.3** Pole position of RC-filter from Problem 2.3 within the complex s-plane as calculated with DST.

# Solution 2.3, cont. 2


The corresponding frequency response can be viewed using the *Show Response* menu from the DST main window using the option *Frequency Response -> Amplitude-> lin-lin* (Fig. A 2.4).



**Fig. A 2.4** Frequency response function (amplitude only) for the pole position shown in Fig. A 2.3.


**Note:** Although the plot in Fig. A 2.4 shows a continuous curve, it is actually a discrete approximation of the continuous frequency response function. The details of the underlying relationship will be explained in detail in chapter 7 “From infinitely continuous to finite discrete”. At this point it is sufficient to know that the internal sampling frequency for the calculation of the frequency response function can be modified in the *Setup* menu. For reasons which are explained in chapter 7, the frequency band which is plotted ranges from 0 to 1/2 of the internal sampling frequency.

# Lin-Lin scale




**Fig. 2.11** Frequency response function (amplitude only) of the RC filter of Problem 2.3.

# Log-Log scale




**Fig. 2.12** Same plot as Fig. 2.11 only on a log-log scale.

# Log-Log scale



**Fig. 2.12** Same plot as Fig. 2.11 only on a log-log scale.

# Log-Log scale



**Fig. 2.12** Same plot as Fig. 2.11 only on a log-log scale.

# Shape of frequency response function

[Corner frequency:  $0,2\text{Hz} = 1/5 \cdot \text{sec}^{-1} = 1/(RC \cdot 2\pi)$ ]

$$|T(j\omega)| = \frac{1}{\tau} \left[ \frac{1}{|(1/\tau) + j\omega|} \right] = \frac{1}{\sqrt{1 + \omega^2 \tau^2}}$$

# Shape of frequency response function

[Corner frequency:  $0,2\text{Hz} = 1/5 \cdot \text{sec}^{-1} = 1/(RC \cdot 2\pi)$ ]

$$|T(j\omega)| = \frac{1}{\tau} \left[ \frac{1}{|(1/\tau) + j\omega|} \right] = \frac{1}{\sqrt{1 + \omega^2 \tau^2}}$$

Definition:  $\omega_c := \left| -\frac{1}{\tau} \right| \quad \Rightarrow \quad |T(j\omega)| = \frac{1}{\sqrt{1 + \frac{\omega^2}{\omega_c^2}}}$

# Shape of frequency response function

[Corner frequency:  $0,2\text{Hz} = 1 / 5 \cdot \text{sec}^{-1} = 1 / (RC \cdot 2\pi)$ ]

$$|T(j\omega)| = \frac{1}{\tau} \left[ \frac{1}{|(1/\tau) + j\omega|} \right] = \frac{1}{\sqrt{1 + \omega^2 \tau^2}}$$

Definition:  $\omega_c := \left| -\frac{1}{\tau} \right| \quad \Longrightarrow \quad |T(j\omega)| = \frac{1}{\sqrt{1 + \frac{\omega^2}{\omega_c^2}}}$

$$\omega \rightarrow 0 : \quad |T(j\omega)| \rightarrow 1 = \text{const}$$

# Shape of frequency response function

[Corner frequency:  $0,2\text{Hz} = 1/5 \cdot \text{sec}^{-1} = 1/(RC \cdot 2\pi)$ ]

$$|T(j\omega)| = \frac{1}{\tau} \left[ \frac{1}{|(1/\tau) + j\omega|} \right] = \frac{1}{\sqrt{1 + \omega^2 \tau^2}}$$

Definition:  $\omega_c := \left| -\frac{1}{\tau} \right| \quad \Longrightarrow \quad |T(j\omega)| = \frac{1}{\sqrt{1 + \frac{\omega^2}{\omega_c^2}}}$

$$\omega \rightarrow 0 : |T(j\omega)| \rightarrow 1 = \text{const}$$

$$\omega \gg \omega_c : |T(j\omega)| \rightarrow \omega^{-1}$$

# Shape of frequency response function

[Corner frequency:  $0,2\text{Hz} = 1/5 \cdot \text{sec}^{-1} = 1/(RC \cdot 2\pi)$ ]

$$|T(j\omega)| = \frac{1}{\tau} \left[ \frac{1}{|(1/\tau) + j\omega|} \right] = \frac{1}{\sqrt{1 + \omega^2 \tau^2}}$$

Definition:  $\omega_c := \left| -\frac{1}{\tau} \right| \quad \Longrightarrow \quad |T(j\omega)| = \frac{1}{\sqrt{1 + \frac{\omega^2}{\omega_c^2}}}$

$$\omega \rightarrow 0 : |T(j\omega)| \rightarrow 1 = \text{const}$$

$$\omega \gg \omega_c : |T(j\omega)| \rightarrow \omega^{-1}$$

$$\text{Slope}_{\log-\log} = \frac{\log_{10} A(\omega_2) - \log_{10} A(\omega_1)}{\log_{10}(\omega_2) - \log_{10}(\omega_1)} = \frac{\log_{10} \left( \frac{A(\omega_2)}{A(\omega_1)} \right)}{\log_{10} \left( \frac{\omega_2}{\omega_1} \right)}$$

## Amplitude ratio in $dB$ ( $20 \log_{10}(\text{amplitude ratio})$ ):

$$Slope_{dB/D\omega} = 20 \cdot \frac{\log_{10} \left( \frac{A(\omega_2)}{A(\omega_1)} \right)}{\log_{10} \left( \frac{\omega_2}{\omega_1} \right)}$$

for  $|T(j\omega)| \gg \omega^{-1}$

amplitude decreases by a factor of 10 over a full decade

$$\text{Therefore } Slope_{dB/dec} = 20 \cdot \frac{\log_{10}(0,1)}{\log_{10}(10)} = -20dB \quad [dB / decade]$$

or following the same argument  $-6 \text{ dB/octave}$

General rule:

Rule: A single pole in the transfer function causes the slope of the amplitude portion of the frequency response function in a log-log plot to decrease by 20 dB/decade or 6 dB/octave, respectively.

# **The RC filter and the role of the pole**

# The RC filter and the role of the pole

Transfer function:  $T(s) = \frac{1}{1 + s\tau}$       pole:  $s_p = -\frac{1}{\tau}$

# The RC filter and the role of the pole

Transfer function:  $T(s) = \frac{1}{1 + s\tau}$       pole:  $s_p = -\frac{1}{\tau}$

- determines boundary of ROC

# The RC filter and the role of the pole

Transfer function:  $T(s) = \frac{1}{1 + s\tau}$       pole:  $s_p = -\frac{1}{\tau}$

- **determines boundary of ROC**
- **position determines stability**

# The RC filter and the role of the pole


Transfer function:  $T(s) = \frac{1}{1 + s\tau}$       pole:  $s_p = -\frac{1}{\tau}$

- **determines boundary of ROC**
- **position determines stability**
- **length of pole vector determines magnification**

$$|T(j\omega)| \sim \left| \frac{1}{\rho(\omega)} \right|$$

# The RC filter and the role of the pole

Transfer function:  $T(s) = \frac{1}{1 + s\tau}$       pole:  $s_p = -\frac{1}{\tau}$



- determines boundary of ROC
- position determines stability
- length of pole vector determines magnification

$$|T(j\omega)| \sim \left| \frac{1}{\rho(\omega)} \right|$$

- a pole in the transfer function changes the slope of the modulus of the frequency response function by  $\omega^{-1}$  (20 dB/dec, 6dB/oct) at a corner frequency  $\omega_c = |s_p|$